

## 2484 Master Disconnect Switch

Two positions: Off-On. For 6-36V DC systems.

Will disconnect the battery circuit only. Electrical Ratings ul listed 375M: 250A at 6V, 125A at 12V intermittent; 40A at 6V, 20A at 12V. Electrical ratings on UL labels are conservative.  
With copper contacts.



### Specifications

|                      |   |
|----------------------|---|
| <b>Description</b>   | Master Disconnect Switch  |
| <b>Details</b>       | Single Pole battery disconnect, Two Positions: Off-On                       |
| <b>UL listed</b>     | UL listed   |
| <b>Rating</b>        | 12V DC; 20A continuous 125A intermittent 15 sec. On, 5 min. Off (UL rating) |
| <b>Terminals</b>     | two 3/8" copper studs   |
| <b>Actuators</b>     | diecast lever   |
| <b>Mounting stem</b> | brass, 3/4" - 16 thread, 23/32" long, fits panel through 3/16" thick        |
| <b>Case</b>          | plated steel  |
| <b>Installation</b>  | Through hole - Clearance for 3/4" dia. mounting stem                        |
| <b>Contacts</b>      | Copper  |

[dwg 2484](#)

### Related Products

**24505**  
Lockout Lever Kit for Master Disconnect Switches

**75920**  
Master Disconnect Switch

**80101-B**  
Chrome-plated cast zinc Lever