

## 75904-02 DPST Master Disconnect Switch

With two Hencol keys.

Two positions: Off-On.

For 6-36V DC systems.

Will disconnect the battery and the alternator or generator field circuit.

Electrical ratings: Large studs: 1000A intermittent. 15 seconds On, 5 minutes Off. 125A continuous.

Small studs: 20A continuous.

Plated steel case.

Silver-laminated contacts.

Brass mounting stem 3/4" -16 thread 17/32" (13.5mm) long. Fits panels through 1/4" (6.4mm) thick.

Two 3/8" -24 and two 10-32 studs.

With indexing pin.




### Specifications

|                      |  |
|----------------------|--|
| <b>Description</b>   | Master Disconnect Switch   |
| <b>Details</b>       | Double Pole, Two Positions: Off-On   |
| <b>UL listed</b>     | not listed   |
| <b>Rating</b>        | 6-36V DC; Large studs 125A continuous - 1000A intermittent, 15 sec. On, 5 min. Off; Small studs 20A continuous |
| <b>Terminals</b>     | two 3/8" copper studs, two 10-32 studs   |
| <b>Actuators</b>     | "Hencol" lock with two keys  |
| <b>Mounting stem</b> | brass, 3/4" - 16 thread, 17/32" long, fits panel through 1/4" thick  |
| <b>Case</b>          | plated steel, with indexing/alignment pin  |
| <b>Installation</b>  | Through holes - Clearance for 3/4" dia. mounting stem and index pin  |
| <b>Contacts</b>      | silver laminated   |

### Related Products

**83353**  
Hencol Key



Commercial Vehicle Products  
20 Old Colony Avenue  
Boston, MA 02127-2467, USA  
+1 617.268.2100