

## 55019 DPDT On-Off-On Toggle Switch

Standard handle.

Universal application.

Silver contacts.

Mounting stem is nickel-plated brass 15/32" -32 thread, 15/32" (11.9mm) long, and fits panels up to 9/32" (7.1mm).



Phenolic housing, with plated steel cap.

Nickel-plated brass mounting hardware.

Six blade terminals: .250 quick connect.

25A at 12V, 15A at 24V, and 10A at 36V DC.

Up: On, Center: Off, Down: On.



### Specifications

Switch type	Toggle
Description	Heavy Duty Toggle Switch
Circuitry	DPDT
Electrical Rating	25A at 12V DC
Contacts	Silver
Housing	Plastic with plated steel cap
Up position	On
Center position	Off
Down position	On
Terminals	6 blade
Handle material	Nickel-plated brass
Handle type	Standard
Handle size: inches	11/16" Long
Handle size: mm	17.46mm
Mounting hardware	Nickel plated brass face and hex nut
Mounting stem material	Nickel plated brass
Mounting stem dimensions	15/32" -32 thread, 15/32" (11.90mm) Long
Mounting hole dimension	15/32" (11.90mm) Panel Hole
Panel thickness	Up to 1/4" (6.35mm) thick

### Related Products

54107

DPDT On-Off-On Toggle Switch

**54107-01**

DPDT On-Off-On Toggle Switch

**55057**

DPDT On-Off-On, Long Handle Toggle Switch

**551806**

DPDT On-Off-On Toggle Switch

**551846**

On-Off-On Toggle Switch

**5592**

DPDT On-Off-On Toggle Switch

**59024-118**

DPDT On-Off-On Toggle Switch

**59024-15**

DPDT On-Off-On Freightliner Toggle Switch

**59024-36**

DPDT On-Off-On Freightliner Toggle Switch



Expertise Applied | Answers Delivered



© 2014 Littelfuse, Inc. All rights reserved. Cole Hersee is a Littelfuse brand.

Commercial Vehicle Products  
20 Old Colony Avenue  
Boston, MA 02127-2467, USA  
+1 617.268.2100