

55054 DPDT Mom On-Off-Mom On Toggle Switch

Standard handle.

Universal application.

Silver contacts.


Mounting stem is nickel-plated brass 15/32" -32 thread, 15/32" (11.9mm) long, and fits panels up to 9/32" (7.1mm).

Phenolic housing, with plated steel cap.

Nickel-plated brass mounting hardware.

Six screw terminals: 6-32 screws. 25A at 12V, 15A at 24V, and 10A at 36V DC.

Up: Mom On, Center: Off, Down: Mom On.



Specifications

Switch type	Toggle
Description	Heavy Duty Toggle Switch
Circuitry	DPDT-Momentary
Electrical Rating	25A at 12V DC
Contacts	Silver
Housing	Plastic with plated steel cap
Up position	Momentary On
Center position	Off
Down position	Momentary On
Terminals	6 screw
Handle material	Nickel-plated brass
Handle type	Standard
Handle size: inches	11/16" Long
Handle size: mm	17.46mm
Mounting hardware	Nickel plated brass face and hex nut
Mounting stem material	Nickel plated brass
Mounting stem dimensions	15/32" -32 thread, 15/32" (11.90mm) Long
Mounting hole dimension	15/32" (11.90mm) Panel Hole
Panel thickness	Up to 1/4" (6.35mm) thick

Related Products

55054-04
DPDT Mom On-Off-Mom On, Long Handle Toggle Switch

55065-02
DPDT Mom On-Off-Mom On, Long Handle Toggle Switch

5543-15
Recessed Faceplate Guard for Toggle Switches

81264-05
Red Toggle Boot Seal

81271
Red Handle Extension for Toggle Switches

82465
Walled Faceplate Switch Guard for Toggle Switches

82468
Flip Cover Switch Guard for Toggle Switches

8250
Nickel-Plated Faceplate for Toggle Switches



Expertise Applied | Answers Delivered



© 2014 Littelfuse, Inc. All rights reserved. Cole Hersee is a Littelfuse brand.

Commercial Vehicle Products
20 Old Colony Avenue
Boston, MA 02127-2467, USA
+1 617.268.2100