

5588 DPST On-Off Toggle Switch

Standard handle. universal application.

Silver contacts.

Mounting stem is nickel-plated brass 15/32" -32 thread, 15/32" (11.9mm) long, and fits panels up to 9/32" (7.1mm).




Phenolic housing, with plated steel cap.

Nickel-plated brass mounting hardware.

Four screw terminals: 6-32 screws.

25A at 12V, 15A at 24V, and 10A at 36V DC.

Up: On, Down: Off.



Specifications

Switch type	Toggle
Description	Heavy Duty Toggle Switch
Circuitry	DPST
Electrical Rating	25A at 12V DC
Contacts	Silver
Housing	Plastic with plated steel cap
Up position	On
Center position	None
Down position	Off
Terminals	4 screw
Handle material	Nickel-plated brass
Handle type	Standard
Handle size: inches	11/16" Long
Handle size: mm	17.46mm
Mounting hardware	Nickel plated brass face and hex nut
Mounting stem material	Nickel plated brass
Mounting stem dimensions	15/32" -32 thread, 15/32" (11.90mm) Long
Mounting hole dimension	15/32" (11.90mm) Panel Hole
Panel thickness	Up to 1/4" (6.35mm) thick

Related Products

5543-15
Recessed Faceplate Guard for Toggle Switches

81264-05
Red Toggle Boot Seal

81271
Red Handle Extension for Toggle Switches

82465
Walled Faceplate Switch Guard for Toggle Switches

82468
Flip Cover Switch Guard for Toggle Switches

8250
Nickel-Plated Faceplate for Toggle Switches



Expertise Applied | Answers Delivered



© 2014 Littelfuse, Inc. All rights reserved. Cole Hersee is a Littelfuse brand.

Commercial Vehicle Products
20 Old Colony Avenue
Boston, MA 02127-2467, USA
+1 617.268.2100