

## 5582 SPST On-Off Toggle Switch

Standard handle. universal application.

Silver contacts.



Mounting stem is nickel-plated brass 15/32" -32 thread, 15/32" (11.9mm) long, and fits panels up to 9/32" (7.1mm).

Phenolic housing, with plated steel cap.

Nickel-plated brass mounting hardware.

Screw terminals: 6-32 screws. 25A at 12V, 15A at 24V, and 10A at 36V DC.

Up: On, Down: Off. Two screw terminals.



### Specifications

|                          |  |
|--------------------------|--|
| Switch type              | Toggle                                   |
| Description              | Heavy Duty Toggle Switch                 |
| Circuitry                | SPST                                     |
| Electrical Rating        | 25A at 12V DC                            |
| Contacts                 | Silver                                   |
| Housing                  | Plastic with plated steel cap            |
| Up position              | On                                       |
| Center position          | None                                     |
| Down position            | Off                                      |
| Terminals                | 2 screw                                  |
| Handle material          | Nickel-plated brass                      |
| Handle type              | Standard                                 |
| Handle size: inches      | 11/16" Long                              |
| Handle size: mm          | 17.46mm                                  |
| Mounting hardware        | Nickel plated brass face and hex nut     |
| Mounting stem material   | Nickel plated brass                      |
| Mounting stem dimensions | 15/32" -32 thread, 15/32" (11.90mm) Long |
| Mounting hole dimension  | 15/32" (11.90mm) Panel Hole              |
| Panel thickness          | Up to 1/4" (6.35mm) thick                |